

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址	<b>Pneumofore S.p.A.</b> Vacuum Pumps and Air Compressors Via Natale Bruno 34 10098 Rivoli
国家	意大利
电话号码	0039 011 950 40 30
传真	0039 011 950 40 40
互联网	www.pneumofore.com
职员	50 - 60
年营业额	10 mio EURO
证书	UNI EN ISO 9001 and ISO 14001
创建年份	1923
出口价格	85 %
协会	GIMAV

## 联系人

Contact 1.	先生 工程学位 Daniel Hilfiker President Phone: 0039 011 950 40 30 Fax: 0039 011 950 40 40
Contact 2.	先生 Rolf Hilfiker CEO Phone: +39 011 950 40 30 Fax: +39 011 950 40 40
Contact 3.	女士 Anastasiia Bratash Area Sales Manager Phone: +39 011 950 40 30 Fax: +39 011 950 40 40

Contact 4.

先生 Gary Wilkinson  
Area Sales Manager

## 产品/机械

Leader in vacuum systems for IS machines, Pneumofore developed the largest air-cooled single stage rotary vane vacuum pump worldwide, the UV100.

### FULL PRODUCT RANGE

To accommodate any customer need or application requirement, we offer different technologies in a wide capacity range.

Pneumofore Rotary Vane Pumps and Compressors lead the market in energy savings: their design ensure long-term efficiency and the cost reduction of maintenance.

Specific solutions can be delivered for most demanding projects to ensure faster ROI or short-term installations. All products are in compliance with CE norms (European Community) and are available for any combination of voltage and frequency.

#### Vacuum Pumps

Sliding vane, single-stage, lubricated, up to 6.610 m<sup>3</sup>/h at 50 Hz and 0,5 mbar(a) residual pressure; up to 6.480 m<sup>3</sup>/h at 60 Hz and 0,5 mbar(a) residual pressure;

#### Air Compressors

Sliding vane, single-stage, lubricated: at 50 Hz, from 5,5 to 400 kW, from 70 to 4.930 m<sup>3</sup>/h, operative pressure from 2,5 to 10 bar(g); at 60 Hz, from 7,5 to 540 kW, from 83 to 5.360 m<sup>3</sup>/h, operative pressure from 2,5 to 10 bar(g).

#### Accessories for Vacuum

Demister Filters for separation of oil mist / graphite lubricant coming from the moulds on the IS machines, capacity up to 5100 m<sup>3</sup>/h;  
Vacuum Receivers, volume up to 10 m<sup>3</sup>.

#### Accessories for Compressed Air

Fridge Dryers, capacity from 12 to 10.800 m<sup>3</sup>/h;  
Adsorption and high pressure Dryers, on request;  
Filters, capacity from 31,8 to 27.000 m<sup>3</sup>/h with residual coolant content down to 0,003 mg/m<sup>3</sup>;  
Air Receivers, tested according to CE regulation, volume up to 10 m<sup>3</sup>.

### SERVICE

Complete customer satisfaction regarding Spare Parts and Maintenance.

Assistance and troubleshooting is guaranteed through a dedicated division of Pneumofore with trained and experienced professionals.

Service Centers available on 5 continents.

### PLANT ENGINEERING

The Pneumofore Engineering Team calculates the pneumatic system layout with all devices from the pump / compressor room to the spot of application. Available for consulting and customer support to respond to case-specific requirements. For new systems, please refer to the "Preliminary Specifications" in the download section.

## 产品和背景

意大利Pneumofore公司是世界真空泵及压缩机制造商的领航者，自1923年成立以来以旋片技术为主导，为全球企业提供丰富的整体产品方案，以专业经验和国际化的服务理念满足不同的客户需求。Pneumofore长期持续致力于降低产品循环使用寿命的成本，并以此为基础带动了集中式真空泵系统的发展潮流，专门应用于玻璃工业以及制瓶机领域。

Pneumofore在创造，发展，制造，安装以及提供自身极富创造力的产品同时，也为整个行业设定了高效，高空气纯度，信赖度以及持久性的标准。

#### Pneumofore产品主要优势

Pneumofore的工程师团队所原创的系列产品方案，从可在极端气候条件下工作的压缩机到全球最大的风冷旋片真空泵，都堪称引领未来行业标准之作。

**耐久性：**旋片真空泵和压缩机配有铝制叶片，坚固的结构可供24小时连续运转。

**低成本以及节能：**丰富的风冷设备系列都可以按照需求调整运转速度，以此达到最优化的循环使用寿命成本和投资回报率。

**易于安装：**“Plug and Play”单元确保在没有地基和水供给的情况也可以使用。

**环保：**在不降低效率的同时，还可确保最低的能耗，不产生冷却剂蒸汽和水污染，以及极低的噪音。

#### Company Profile of **Pneumofore S.p.A.**

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用，风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH