

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址	SMAC Moving Coil Actuators 5807 Van Allen Way Carlsbad 92008
国家	美国
州	California

产品/机械

SMAC Electric Actuators make glass processing easier.

SMAC electric actuators incorporate programmable speeds, positions, and, especially importantly for glass, programmable forces including very low forces on the order of 0.1N or less. SMAC electric actuators also incorporate a patented "Soft-Land" capability, which is very useful when applied to brittle materials. The force programmability works over the complete stroke, so the same force can be applied through the stroke. Soft-Land incorporates a rapid approach to the working surface followed by a gentle pre-programmed force for final contact.

Measuring Thickness of Thin Flexible Glass

Problem: Accuracy of the current air cylinder, LVDT and force control system.

Solution: The customer used the Soft-Land feature of the SMAC LAL20 in conjunction with a load cell mounted on the rod of the SMAC actuator. The LAL20 is controlled by a dual-axis LAC25.

Inspection of the Curvature of Automotive and Aircraft Window Glass

Problem: Accuracy of the current air cylinder, LVDT and force control system, short life of LVDT, time consuming position calibration.

Solution: The two original pneumatic cylinders for centering the windscreen were replaced by two LAL95-015 units. Two of the six pneumatic cylinders for position measurement were not needed anymore. The LAL95 provides both positioning and measurement functions. All other sensors, mechanical and electronic parts were unchanged. 100% QC/QA in-line inspection now possible during production.

Glass Grinding

Problem: The grinding process produces a 125µm finish with less than a 50µm variation. Damage to glass at the beginning and end of the grind cycle is caused by inadequate force control of the air cylinder driving the grind wheel. The force required is from two to four Newtons, with a 5mm stroke.

Solution: Customer was able to land softly on the glass panel and provide a constant force using the "force mode" of the LAL55 at both the beginning and end of the stroke.

Company Profile of SMAC Moving Coil Actuators

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理, 保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用, 风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH