

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址	ODE Yalıtım Sanayii ve Ticaret A.S. Production Site Hacı Seremet Mevkii 3. Sok. Çorlu Tekirdağ
国家	土耳其

产品/机械

ODE STARFLEX

Technical Specifications

Thermal Conductivity Coefficient 0,040 W/mK

Density 12-1000 kg/m3

Fire Classification TS EN 13501-1 A Class

Temperature Range -50°C -+ 250°C

- * Produced with the transformation of silica sand into fiber by melting in high temperature.
- * Used for thermal insulation, acoustic insulation, acoustic arrangement and fire safety purposes.
- * Can be produced in the forms of blanket, Board, pipe and cast with various coating materials in different sizes and technical specifications depending on the area and purpose of use.
- * TSE Certificate of Conformity
- * CE Mark

Advantages

- * Does not allow water passage and remains dry with its water repellent characteristic.
- * Is a Class A incombustible insulation material.
- * Not hygroscopic and capillary.
- * Can not be destroyed by insects or microorganisms.
- * Does not deteriorate, decay, mould, corrode or rust over time.

Company Profile of ODE Yalıtım Sanayii ve Ticaret A.S.

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用，风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH