

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.[OK](#)[Details](#)

地址	Rongju Machinery & Electronic Co.,Ltd No.3 Iiji lane, 2nd Xiaobian industrial area, 523840 Dongguan
国家	中国 (中华人民共和国)

产品/机械

Specifications:

Operating Temperature Range:-50~+105 Degree Celsius.

Rated Voltage Range:6.3v~100v DC.

Nominal Capacitance Range:0.47uF~1500uF

Capacitance Tolerance: ±20%(126Hz, ±20Degree Celsius)

Leakage Current: \leq 0.01CRUR(uA)or 3uA whichever is greater(after 2minutes)

Dissipation Factor(120Hz 20C):Ur(V) 6.3~100, tg\$:0.12~0.30

Load Life: After applying rated voltage for 2000 hours at +105C and then resumed 16 hours, the capacitor shall meet the following limits:

Capacitance Change \leq ±30% Initial measured value

Leakage \leq Initial specified value

Dissipation Factor \leq 300% of initial specified value

Shelf Life: After storage 1000 hours at +105C and then resumed 16 hours, the capacitor shall meet the following limits:

Capacitance Change \leq ±30% Initial measured value

Leakage \leq 200% of Initial specified value

Dissipation Factor \leq 300% of initial specified value

Resistance to soldering Heat: The capacitors shall be kept on the hot plate maintained at 250C for 30 seconds. After removing from the hot plate and restored at room temperature, then meet the following requirement:

Capacitance Change \leq ±10% Initial measured value

Leakage \leq Initial specified value

Dissipation Factor \leq Initial specified value

Company Profile of Rongju Machinery & Electronic Co.,Ltd

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用，并且用户对材料的用途和使用，风险自担。禁止对其他的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供，使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH