

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

---

地址 **Sicherheitsglastechnik Oelsnitz (Vogtl.) GmbH**  
Talstraße 2  
D-08606 Oelsnitz (Vogtl.)

---

国家 德国

## 产品/机械

Toughened Glass

Toughened safety glass is made via a thermal toughening process. A heating and cooling process distribute the stress in the glass. The glass is heated to a temperature above 620°C, and then air-cooled. This sudden cooling induces tensile stresses in the centre of the glass balanced by compressive stresses in the surface.

If broken, this equilibrium of stresses is destroyed and the glass crumbles into small pieces that have blunt edges. The benefits of toughened safety glass are its increased bending, impact, shock and thermal shock resistance.

As a result of its safety toughened safety glass can be used for exterior and interior applications.

### Product Range / Production Options Toughened Glass

- Maximum size 9,000mm x 3,300mm
- Thickness range between 4mm - 19mm
- Edge working
- Mitered edges
- Drilled holes
- Countersunk holes
- Corner cut-outs
- Edge cut-outs
- Centre cut-outs
- Round corners
- Shaped glass
- Fully enamelled glass, screen printing

### Heat Strengthened Glass

Heat strengthened glass undergoes a similar manufacturing process as toughened glass. The only difference is the significantly slower cooling process. By cooling the glass at a slower pace less stress is induced in the glass. This results in heat strengthened glass having a similar breakage pattern as float glass. Heat strengthened glass can only be regarded as safety glass when used in laminated glass.

### Product Range / Production Options Heat Strengthened Glass

- Maximum size 9,000mm x 3,300mm
- Thickness range between 4mm - 12mm
- Edge working
- Mitered edges
- Drilled holes
- Countersunk holes
- Corner cut-outs
- Edge cut-outs
- Centre cut-outs
- Round corners
- Shaped glass
- Fully enamelled glass, screen printing

### Laminated Safety Glass

Laminated safety glass consists of at least two panes of either float glass, toughened glass or heat strengthened glass firmly bonded with viscoelastic, highly tear resistant Polyvinyl Butyral (PVB) interlayers.

In the event of breakage, the glass fragments are retained by the interlayer. The thickness of the interlayer affects the remaining load capacity. The benefits of laminated safety glass are its bending and impact resistance and its ability to resist high temperatures. Depending on the panes, SGT's laminated safety glass has the following benefits:

- protection from glass fallout in overhead glazing
- impact resistance
- intrusion resistance
- blast resistance

#### Product Range / Production Options Laminated Safety Glass

- Maximum size 9,000mm x 3,300mm
- Thickness range between 4mm - 19mm
- Edge working
- Mitered edges
- Drilled holes
- Countersunk holes
- Corner cut-outs
- Edge cut-outs
- Centre cut-outs
- Round corners
- Shaped glass
- Fully enamelled glass, screen printing

#### Enamelling

SGT uses enamels to provide toughened glass in a range of different colours. Enamels can be applied onto any smooth-surfaced flat glass that can be toughened. The enamels are rolled onto the surface and then fired onto the glass at temperatures between 600 and 620°C. Please note that due to applying the enamels by rolling, the entire glass sheet will be enamelled.

#### Screen printing

#### Company Profile of **Sicherheitsglastechnik Oelsnitz (Vogtl.) GmbH**

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权属于属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用，并且用户对材料的用途和使用，风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供，使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH