

Community



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址	GlasStress Ltd. Glass stress measurement equipment 21/1 Akadeemia Str. 12618 Tallinn
国家	爱沙尼亚
电话号码	00372 655 5531
传真	00372 655 5532
互联网	www.glasstress.com
职员	5
创建年份	2003
出口价格	100 %

联系人

Contact 1. 先生 Johan Anton

CEO

Phone: 00372 655 5531 Fax: 00372 655 5532

产品/机械

Initially, GlasStress Ltd supplied instruments for laboratory use. Developments now concentrates on higher volume lower cost stress analysis equipment that may also be implemented as quality control instruments at the production line. The personnel of GlasStress Ltd has 50 years of experience in measuring stress in glass articles.

At the moment, the most sellable machine is scattered light polariscopes SCALP-05. GlasStress Ltd offers also automatic transmission polariscope AP-07 and scattered light polariscopes SCALP-04.

Scattered light polariscopes are meant for through-the-thickness stress measurement. SCALP-04 is suitable for stress measurement in architectural glass panels and automotive glazing. SCALP-05 is meant for stress measurement in automotive and solar glasses, also in chemically tempered glasses. Both polariscopes are computer controlled. Handling of the polariscopes is extremely simple: just place the the device on the glass panel to be measured and press slightly the button on the left side of the device. After ten seconds the stress profile through the panel thickness is shown on the screen of the laptop.

Polariscope AP-07 is a computer controlled device designed for automatic stress measurement in solid and hollow axisymmetric glass products (drinking glasses, bottles, neck tubes of CRT bulbs, lamps, optical fibre preforms, etc.). It permits also edge stress measurement in glass plates and automotive glazing, thickness stress measurement in strips cut out from glass plates, and measurement of stress at edge corners. Photoelastic measurements are completely automatic and take from 2 to 15 seconds. After that stress distiribution in any section of the test object can be displayed on the screen. Integrated photoelasticity algorithms are used for stress calculation from the measurement data. The polariscope can be used for stress measurement near the production line. Its handling does not need any knowledge about photoelasticity or stress analysis.

glassglobal Community



产品和背景

GlasStress Ltd is a manufacturer of internal residual stress measurement equipment for glass products. GlasSterss Ltd offers automatic transmission polariscopes AP for container, tableware, lighting industries and scattered light polariscopes SCALP for automotive, architectural, solar industries.

Company Profile of GlasStress Ltd.

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理,保留所有权。任何用户访问这样的资料的只限于个人使用,并且用户对材料的用途和使用,风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供,使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH