



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址 VETRO TOOL S.A.
Polígono Industrial de Caborana
33684 Aller - Asturias

国家 西班牙

产品/机械

5 differents types of process:

- · Continuos flat glass tempering.
- · Press bending and tempering of small curvature spherical glasses.
- Press bending and tempering of medium and great curvature spherical glasses.
- · Continuous cylindrical glasses bending and tempering.
- Continuous doble curvature cylindrical glasses bending and tempering.

Changes between each kind of process and/or different models takes less than 5 minutes.

Loading and saving of model parameters on PC.

Short cadences:

- 2-5 seconds/piece of continuous side lite bending and tempering.
- 4-10 seconds/piece on press bending and tempering back lites.
- Very accurate and repetitive, obtaining and optimal tempering.

Specifications:

- Max dimensions: 1250 x 850 mm, for side lites and small back lites.
- Min thickness: 2,8 mm.

Company Profile of VETRO TOOL S.A.

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理,保留所有权。任何用户访问这样的资料的只限于个人使用,并且用户对材料的用途和使用,风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供,使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH