

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址	Suzhou Hengchang Longye Industrial Zhaiji Industrial Park Wangting Tow 215155 Suzhou
国家	中国（中华人民共和国）

产品/机械

Tempered glass
Hollow glass
Laminated glass
Hot bending glass
Appliance glass

The process of Tempered glass is to heat the original glass to the temperature of about 700 °C , and then cool it down rapidly to form the surface compressive on the glass. The Tempered glass can be divided as fully tempered glass and heat strengthened glass (also called partially tempered glass).

Performnce and characteristics:

Tempered glass has roughly there to four times as much resistance to anti-shaking as same thickness of ordinary glass. When the glass breaks caused by external the force of the glass shatters instantly and free of sharp pieces. So as lessen or avoid the injury to human body. Tempered glass can stands the rapid temperature difference (For example: 5mm thickness Tempered glass can stand 200 °C temperature difference.)

Heatrenghed glass features:

Hs glass has roughly twice or three times as much resistance to anti-shocking as same thickness ordinary glass. When the glass breaks caused by external force. The cracks extend from the shooting point to the edge and form the shooting point to the edge and form the radiating shape and most of the broken glass pieces remain in the frame, so as to lessen and avoid the injury to human body. The surface quality is better than Tempered glass.

Application of the product:

Windows and other partials of buildings. Glass partitions and elevator partitions. Windows of automation and ships. Glass tables and showing cases. Interior decoration and glass furniture.

The product characterustic of HCL tempered glass:

1. It is more flat in the level and smooth degree: The biggest characteristic that tempered stove of Finland TAMGLASS is best on the glass level and smooth degree. HCL tempered glass production line imported from Finland TAMGLASS, HCL Tempered glass can satisfy the needs by the level and smooth degree to the stylization such as the building Coated glass and the double layer, mould, And furniture and high layer etc.
2. It is best on temper surface quality: HCL chooses high quality float glass of home and abroad, Using international advanced HCL glass to process equipment temper technology technical standard and control.

Specification of the product:

Max size : 5400mm × 2400mm

Min size: 350mm × 100mm

Thickness: 4mm-19mm

Standards of product: GB/15763.2-2005

Company Profile of **Suzhou Hengchang Longye Industrial**

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用，并且用户对材料的用途和使用，风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供，使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH