

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址	Shandong Yaohua Glass Co.,Ltd No.7 Kuaiyuan Road Wangsheren Town 250101 Jinan City
国家	中国（中华人民共和国）

产品/机械

Products:

New low E insulation glass

insulation glass
laminated glass
tempered glass

You can combination of these. E.g. tempered laminated and insulation glass

curved or bent tempered glass
glass curtain wall
Bulletproof glass
Art glass

Introduce for product

Insulation Glass

Insulation glass solutions from yaohua glass consist of two or three panes of glass that are hermetically sealed. Insulating units reduce heat gained and lost between interior and exterior spaces, contributing to outstanding overall energy efficiency.

Thickness:3mm-15mm

Specification:

Max:2440mmx6000mm

Min: 200mmx300mm

Tempered Glass

Tempered glass offers outstanding safety protection, as it breaks into small, pebble-like pieces. Tempered glasses are ideal for any area where high traffic and human contact may pose safety concerns.

Thickness:4mm-19mm

Specification:

Max:3000mmx8000mm

Laminated Glass

Laminated products consist of two or more glass lites bonded together by a plastic interlayer of polyvinyl butyral (PVB) under heat and pressure. The resulting laminated product—which is visually indistinguishable from monolithic glass

Laminated products provide excellent personal protection when used as safety glazings in commercial buildings of all types. While the surface of laminated products may be broken, the resulting glass shards stay bonded to the PVB plastic interlayer and typically stays on the window or door frame—making them a perfect safety solution when glass be breakaged.

Thickness:3mm-19mm

Specification:

Max:2440x7000mm

Low-E Insulation Glass

The low-E insulation glass can save energy and protect climate through the reduction of carbon dioxide emissions and increased efficiency of components that consume energy – such as reducing the energy consumption of buildings.

The low-E insulation glass gives windows outstanding thermal insulation, while at the same time the warming infrared radiation can enter the building and create solar heating.

Thickness:3-15mm

Specification:

Max:3660x2440mm

Min: 200x300mm

Hot bent Glass

For various areas of application with high technical and aesthetic requirements. For more creativity in order to satisfy building industry.

Thickness:3-19mm

Specification:

Max: 3500x2500mm

Max bent: 650mm

Bent tempered glass

Tempering of curved or bent glass for added strength,safety or both.

There has been an increasing demand for curved or bent tempered glass in buildings and other commercial applications. More curved or bent glass to be used exteriorly in building facades and interiorly in many unique applications in order to create more efficient and dramatic effects.

Thickness:3-19mm

Specification:

Max:3000mmx5000mm

R=1500mm

Company Profile of Shandong Yaohua Glass Co.,Ltd

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理, 保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用, 风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH