



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

产品/机械

Bauxite Brick Andalusite Brick Mullite Brick

Blast Furnace Performance

This range normally falls between 50% and 90% alumina, ie. having refractoriness of over SK35. The normal raw material constituents are alumina in the form of bauxite, Andalusite, Mullite or sintered / fused alumina.

Good strengths, thermal shock resistance, good / high corrosion resistance and alkali resistance are just some of the properties found within these products.

Typical applications include:

re-heating furnaces – ladles – EAF roofs – incinerators – heat treatment furnaces (reducing atmospheres where low iron is necessary) – furnace hearths – cement / lime shaft kilns – ceramic kilns and rotary furnaces etc.

Predominant applications:

ferrous – non ferrous – cement / lime incineration etc.

We have numerous supply lines of quality material and below is an example typical data sheet of one of those options.

Company Profile of Jay's Refractory Specialists Limited

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理,保留所有权。任何用户访问这样的资料的只限于个人使用,并且用户对材料的用途和使用,风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供,使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH