



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址
China Guangdong PVD Metallizer Co.
Guangdong Zhenhua Technology
Yungui road, Zhaoqing Avenue West Block. Zhaoqing, Guangdong, China
526000 Zhaoqing

国家
中国(中华人民共和国)

产品/机械

Horizontal continuous production line for VIP vacuum insulated panel

Our company produces various models of production line for vacuum insulated panel (VIP) as per customers technical requirements, enabling to meet their actual demands. Model XF2000-V/S production line for VIP/STP vacuum insulated panel with structure of the world's first horizontal continuous production line, with features of stable good quality and high efficiency, is an exclusive one in the world and it can achieve the capacity of 8 pieces per minute of VIP/STP panels sized 600X400X65mm. (Specifications of VIP/STP panels can be made as per customers specific demands and requirements. Maximum VIP/STP panel size 1500mmX2000mmX55mm.). Vacuum insulated panel (referred to as VIP in short form) is a newly developed efficient insulation material in recent years with very low thermal conductivity. Its structure consists of 3 parts as insulation material in the core, gas collecting material called Getter and membrane walls used to prevent air from entering the panel called Barrier. It is made by the principle of vacuum insulation through powerful evacuation with vacuum pumps to realize the maximum internal vacuum pressure to prevent heat conduction, which can effectively avoid the three ways as conduction, convection and radiation to achieve insulation and energy-saving purposes. Vacuum insulated panel, one of the vacuum insulation material with low thermal conductivity and excellent properties of thermal insulation and environmental protection, is currently the world's most efficient insulation products. It is a perfect substitute for traditional insulation material and products, extensively used in refrigerators, freezers, water heaters, refrigerated containers, building materials for facades or exterior walls. Its thermal conductivity can be achieved less than 1.5mw/m.k.

Company Profile of China Guangdong PVD Metallizer Co.

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理,保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用,风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH