

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

|    |                                                                          |
|----|--------------------------------------------------------------------------|
| 地址 | <b>Heat Recovery Sweden AB</b><br>Fiskhammsgatan 4<br>SE-414 58 Göteborg |
| 国家 | 瑞典                                                                       |

## 产品/机械

### Double shell recuperators

The double shell recuperator is built up of two concentric cylinders of special steel. Flue gas is led in the center and combustion air is heated in the annulus between the cylinders. The flow direction for the fluegas can be upwards or downwards. Air flow is mostly parrallel but can also be counter flow.

For fluegas directions upwards the double shell works also as a stack. A cone with dampers works as furnace pressure control. Waste gases are leaving either to atmosphere or are led to a filter.

A double shell recuperator work for combustion air preheat up to 600°C.

### Tube bundle recuperators

A tube bundle type of recuperator is built like a tube row in the periferree of a vertical cylinder. This cylinder is built of carbon steel internally insulated by refractory lining materials. The refractory ling materils consists of insulation materials and closest to the flue gas, different types of heat and corrosion resistant bricks.

The flow direction for the fluegas can be upwards or downwards. Air flow is mostly parrallel but can also be counter flow.

For fluegas directions upwards the recuperator works also as a stack. A cone with dampers works as furnace pressure control. Waste gases are leaving either to atmosphere or are led to a filter.

A tube bundle recuperator works for combustion air preheat up to 750°C.

### Two stage recuperators

A two stage recuperator is mostly built up of a double shell mounted on top of and in serie with a tube bundle. The recuperator works also as a stack. A cone with dampers works as furnace pressure control. Waste gases are leaving either to atmosphere or are led to a filter.

A two stage recuperator works for combustion air preheat up to 825°C.

### Company Profile of Heat Recovery Sweden AB

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用，并且用户对材料的用途和使用，风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供，使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH