

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

| | |
|----|--|
| 地址 | Shandong Hongrui Petrochemical Co., Ltd. Shandong Pingyin Industrial Park, 250400 Jinan |
|----|--|

| | |
|----|-------------|
| 国家 | 中国（中华人民共和国） |
|----|-------------|

产品/机械

HRD Polyisobutylene - Typical properties:

Transparent, yellowish, semi-solid, odorless, non-toxic. Polyisobutylene is used for butyl sealants and adhesives, providing strong adhesion and flexibility, as well as an excellent barrier to moisture and gas, making finished products more energy-efficient and durable.

Applications:

1. Hot melt butyl sealants/Insulating glass sealants/double glazing sealants/Primary sealants.
2. Butyl sealing tapes.
3. Pressure sensitive adhesive.
4. Lubricant greases.

Company Profile of **Shandong Hongrui Petrochemical Co., Ltd.**

A service of glasssglobal.com, an affiliate of glasssglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理，保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用，风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glasssglobal.com - 国际性的玻璃工业门户 - OGIS GmbH