## glassglobal

## Community



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

地址 Pro-Sight
Unit 8, Shaw Cross Court
Shaw Cross Business Park
Dewsbury
WF12 7RF

. \_ . . . .

国家

1. Pro-Sight One & Two

One: Single Camera Universal Inspection System

Two: Dual Camera Universal Inspection System

英国

Single or double camera inspection

Defect or region specific inspection

Mobile - can be moved from line to line

Option to add stress inspection

2. Finish Inspector

Sealing Surface / Finish Inspection

Mobile - Can be moved from line to line

Non-contact - no need to rotate the bottle

3. Wall Thickness Measurement

Hot & Cold End

Single sensor used to measure either Hot or Cold Bottles

Non-contact thickness measurements

Hot or cold bottles - 5 to 500 degrees Celsius

Full bottle scanning

Up to 200 measurement points per bottle

User friendly set-up

Accuracy to 0.01mm

4. Base Inspection

Single Camera
Base Inspection System
Can be mounted over a break in
your conveyor, or with a Pro-Sight supplied 'Bolt-On Bypass' with Carryover

5. Base Code Reader

Mould number rejection by reading alphanumeric code on the base of the container.

Can be mounted over a break in your conveyor, or with a Pro-Sight supplied 'Bolt-On Bypass'.

User Friendly set-up

# glassglobal

## Community



Up to 200 BPM

Optional bolt-on bypass removes the need for a break in your conveyor

6. Mould Fin Detector

Sensors that detect and reject containers with sharp seams, pinched necks or offset moulds.

Can be installed on your existing rotating machine (EG: M machine, FP, Check Detector)

User Friendly Set-Up

Up to 200 BPM

Reject counter with alarm

#### 7. Servo Orientator

User friendly high-speed Orientator with integrated bottle separation

Upstream and downstream line control & automatic belt speed tracking. 200 bpm.

#### 8. Carryover

- Enables Base Inspection and / or Base Mould Number Reading
- · Optional bolt on bypass removes the need for a break in your conveyor

#### 9. Star Wheel Separator

- Reversible wheel for left or right hand operation
- · With or without control panel
- · Direct drive

### Company Profile of Pro-Sight

A service of glassglobal.com, an affiliate of glassglobal group.

您出版的地址材料版权是属于公司或对它的第三者销售代理,保留所有权。任何用户访问这样的资料的只限于个人使用, 并且用户对材料的用途和使用,风险自担。禁止对其它的贸易广告及地址资料重新发布。这样的地址材料如果是由第三方提供, 使用这样的新闻材料必须由各用户同意和遵守具体使用条款。Glass Global不保证从任何链接或其它网址打印输出的信息的准确性和可靠性。www.glassglobal.com - 国际性的玻璃工业门户 - OGIS GmbH